



- ventilator diagonal cu stator
- carcasa metalica tabla zincata
- turatie reglabila
- termocontact integrat
- Include consola de montaj

**230V 50Hz**

punct de functionare		1	2	3	4	5
curent	I A	2.04	1.63	2.28	2.27	2.05
consum de putere	P <sub>i</sub> W	460	370	510	510	460
turatie	n 1/min	2790	2850	2760	2760	2800
put. fonica aspiratie	L <sub>WA5</sub> dB (A)	-	80	76	77	81
put. fonica refulare	L <sub>WA6</sub> dB (A)	-	85	82	83	85
put. fonica radiatie	L <sub>WA2</sub> dB (A)	-	63	60	61	63

  

tensiunea	U <sub>N</sub>	230V ~	reglaj turatie	V
curent	I <sub>N</sub>	2.3 A	protectie motor	TMO
curent	I <sub>max</sub>	3.2 A	condensator	10 µF / 400 V
temperatura ambianta	t <sub>U</sub>	55 °C	clasa de izolare	F
temperatura medie	t <sub>F</sub>	55 °C	numarul de poli	2
			greutate	14,15 kg

**accesorii pentru EL 315 E2 01**  
 pentru mai multe informatii vezi internet

- TEM 035 transformator in 5 trepte cu protectie motor
- TES 035 transformator 7 trepte fara protectie motor
- GS 01 comutator
- VM 315 manseta de legatura pentru reducerea zgomotului si vibratiilor
- RSK 315 clapeta anti-retur
- RSK 315D clapeta anti-retur cu izolare
- SG 315 01 grilaj de protectie
- SG 315 02 grilaj de protectie
- SDS 315 atenuator de zgomot rigid
- SDF 315 atenuator de zgomot flexibil
- FV 315 cutie filtranta cu filtru material G3
- FT 315 cutie filtranta pentru filtru cu buzu fara filtru

