



- ventilator centrifugal cu palete orientate inapoi
- carcasa metal RAL 7035
- turatie reglabila
- termocontact integrat

230V 50Hz

punct de functionare		1	2	3	4	5
curent	I A	0,68	0,87	1,26	1,09	0,94
consum de putere	P _t W	150	200	290	250	220
turatie	n 1/min	2780	2540	2260	2460	2590
put. fonica aspirata	L _{WA} dB (A)	-	77	69	74	76
put. fonica refulare	L _{WR} dB (A)	-	79	74	79	81
put. fonica radiatie	L _{WR} dB (A)	-	68	58	62	63
Tensiunea	U _N	230V ~	reglaj turatie			V
curent	I _N	1,3 A	protectie motor			TAI
curent	I _{max}	1,3 A	condensator			8 μF / 400 V
temperatura ambianta	t _a	60 °C	clasa de izolare			F
temperatura medie	t _m	60 °C	numarul de poli			2
			greutate			6,11 kg

accesorii pentru RS 315L

pentru mai multe informatii vezi internet

-  MTY 2 regulator electronic continuu
-  ETY 15 regulator electronic continuu
-  TEE 015 transformator in 5 trepte fara protectie motor
-  TES 0145 transformator 7 trepte fara protectie motor
-  OS 01 comutator
-  MRS 2 consola de montaj pentru ventilata pt tubajul RS
-  VM 315 manseta de legatura pentru reducerea zgomotului si vibratiilor
-  RSK 315 clapeta anti-retur
-  RSK 315D clapeta anti-retur cu botita
-  SG 315 01 grilaj de protectie
-  SDS 315 atenuator de zgomot rigid
-  SDF 315 atenuator de zgomot flexibil

